



■ : SOLDER AREA
 TOLERANCE: ±0.05
 RECOMMENDED PCB LAYOUT
 (TOP VIEW)

Circuit No.	Dimensions						
	A	B (A+5.1)	C (A+1.65)	D (A+1.0)	E (A+2.3)	F (A+3.0)	G (A+4.1)
2*30P	14.50	19.60	16.15	15.50	16.80	17.50	18.60

C 28 0 0 X X -08

Series No. **C2800XX-01**
C2800XX-04
C2800XX-06

Number of Contact **60 Contact**

RoHS compliant

L/TR	Part Name	Material	Description	QTY
1	Housing	LCP UL94V-0	+30%GF 260°C for 10 Seconds. Initial : 1000M Ohms Min.	1
2	Contact	Bronze C5191	Current Rating : 0.5 A Initial : 30m Ohms Max.	XX
3	Fitting Nail	Brass C2680	Current Rating : 0.5 A Initial : 30m Ohms Max.	2

Temperature Rating : -40°C ~ +105°C.
 Dielectric Withstanding Voltage : 300 V AC/Min

THIS DRAWING IS A CONTROLLED DOCUMENT.

DMN	尹晚開	01SEP2023	NAME	CHUFON TECH CO., LTD
CHK	楊廣文	01SEP2023	SIZE	A3
APVD	林振偉	01SEP2023	CAGE CODE	00779
PRODUCT SPEC			DRAWING NO	C280000-08
QUALIFICATION TEST REPORT			SCALE	—
WEIGHT			SHEET	1 OF 1
CUSTOMER DRAWING			REV	A0

PH0.5 BTOB H2.5 公座

RESTRICTED TO