



C 28 00 XX -11

Number of Contact
30 Contact

Series No.
MATE WITH C2800XX-09

LTR	Part Name	Material	Description	QTY
1	Housing	LCP UL94V-0	260°C for 10 Seconds, Initial : 1000M Ohms Min.	1
2	Contact	Bronze	Current Rating : 0.5 A Initial : 30m Ohms Max.	XX

Temperature Rating : -40°C ~ +105°C.
Dielectric Withstanding Voltage : 300 V AC/Min

: SOLDER AREA

TOLERANCE: ±0.05,
RECOMMENDED PCB LAYOUT
(TOP VIEW)

Circuit No.	Dimensions			
	A	B (A+4.3)	C (A+2.0)	D (A+2.6)
2*15P	7.00	11.30	9.00	9.60
2*20P	9.50	13.80	11.50	12.10

THIS DRAWING IS A CONTROLLED DOCUMENT.

DMN 尹晚開 01SEP2023
CHK 楊廣文 01SEP2023
APVD 林振偉 01SEP2023

NAME
CHUFON TECH CO., LTD

PH0.5 BT0B H0.95 & 4.0 公座

DIMENSIONS: MM	TOLERANCES UNLESS OTHERWISE SPECIFIED:	QUALIFICATION TEST REPORT	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO	
0 P.L.C ± -	1 P.L.C ± 0.30	/	A3	00779	C280000-11	-	
2 P.L.C ± 0.20	3 P.L.C ± 0.15		SCALE	1	SHEET	1	REV
4 P.L.C ± 0.15	ANGLES ± 3°		CUSTOMER DRAWING	1	OF	1	AO